

Each "easy-change" cartridge becomes an integral part of the machine with no compromise on its ability to perform the required function. Whether it be mowing, scarification, verti-cutting or sweeping, such versatility allows much greater seasonal use of the power unit increasing the value of the investment.

This superb lightweight sports ground mower is not only perfect for soccer pitches where compaction is a problem, but also for large areas of formal lawns, where the collection of grass and a beautiful striped effect are required. An optional trailing seat can be used to increase efficiency on larger areas. In common with all other Allett mowers, height and cutter adjustments are very easy on the C34.

Designed to run on low engine revs., the machine is very smooth, quiet and economical to operate.

The rear roller is in three sections and is rubber covered for good traction and silent running over hard surfaces. Internally, the rear roller is fitted with hardened steel differential gears, which run in a sealed oil bath. The optional trailing seat also has a rubber covered roller.

The mower has a low profile for good forward visibility. The C34 is very robust and both long life and easy servicing are assured.

Call us now and ask for a demonstration.

# C34











Overall Width
Overall Length
Overall Height
Weight
Drive Clutch

**Cutter Clutch** 

Rear Roller Differential Front Roller Handle Bar Grassbox

### **Optional Extra**

6 blade cylinder
Rate of cut
Cylinder

Bottom Blade Height of Cut

8 blade cylinder
Rate of cut
Cylinder

Bottom Blade Height of Cut

> C34SC Scarifier

C34SL Verticut

> C34B Brush

## S p e c i f i c a t i o n s

Power unit

Honda GX200 6.5 HP Petrol

1168mm

1775mm

1020mm

164 KG

Handle mounted lever operating tight and loose twin

belts via a cable

Handle mounted lever operating tight and loose triple

belts via a cable

Three piece steel sections, rubber covered

Hardened steel gears running in a sealed oil bath

Aluminium running on sealed bearings Adjustable with anti vibration mounts

Rotationally moulded plastic with steel reinforcing strip

### Trailing seat

### Cartridge options

Weight Working Width Overall Width 43kg 863mm 978mm

94 cuts per metre (86 cuts per yard 2.39 cuts per inch)
All welded, high carbon steel Hardened and tempered to 45HRC.

Manufactured from EN8, hardened and tempered to 45HRC 8mm to 55 mm

Weight Working Width Overall Width

45kg 863mm 978mm

125 cuts per metre (114 cuts per yard 3.18 cuts per inch)
All welded, high carbon steel Hardened and tempered to 45HRC.

Manufactured from EN8, hardened and tempered to 45HRC 8mm to 55 mm

Weight Working Width Overall Width

29kg 863mm 978mm 38 High carbon spring steel blades at 20mm spacing

Maight Marking Width Overall Width

Weight Working Width Overall Width 30kg 863mm 978mm

52 High carbon spring steel blades at 15mm spacing

Weight 25kg Working Width 978mm

6 rows of 1.25mm Polypropylene bristles